

Title: CHILD-RESISTANT UTILITY LIGHTER INCORPORATING
A CAM MECHANISM AND A LEVER SPRING LOCK

Inventor: Kil Yong Sung

Atty Dkt No.: 01-12-1826

5 Express Mail Label Number: EL732937866US

I hereby certify that this correspondence is being deposited with the U.S. Postal Service as EXPRESS MAIL, postage prepaid, under 37 CFR 1.10 in an envelope addressed to: U.S. Patent and Trademark Office, Box Patent Application, Arlington, VA 22202 on 3 December 2001.

10

By: David Hong
David Hong (#45,704)

RELATED PATENT APPLICATIONS

15 This application is a continuation of Serial No. 09/794,989, filed February 26, 2001, now U.S. Patent No. 6,325,617 issued December 4, 2001, which is a continuation of the following applications:

20 Serial No. 09/751,628, filed December 30, 2000, which claims priority to Serial No. 09/531,082, filed March 18, 2000, now U.S. Patent No. 6,168,420 issued on January 2, 2001, which claims priority to Serial No. 09/507,100, filed February 17, 2000, now U.S. Patent No. 6,186,773 issued on February 13, 2001, which claims priority to Provisional Application Serial No. 60/126,326,
25 filed March 26, 1999;

Serial No. 09/716,573, filed November 17, 2000, which claims priority to Serial No. 09/507,100, filed February 17, 2000, now U.S. Patent No. 6,186,773 issued on February 13, 2001; and

Serial No. 09/572,509, filed May 18, 2000, which claims
30 priority to Serial No. 09/531,083, filed March 18, 2000.

BACKGROUND OF INVENTION

1. FIELD OF INVENTION:

This invention relates to a utility lighter which contains a safety feature incorporating a cam mechanism and a safety button, wherein normal operation of the lighter through depression of the trigger is impeded by the safety feature, and wherein operation of both the safety button and the trigger will produce a flame.

This invention also relates to a utility lighter which contains a safety feature incorporating a safety button or release lever, wherein the safety button slides forward to operate the fuel-release valve and unlock the trigger.

2. BACKGROUND ART:

Utility lighters are very useful and have become quite prevalent in modern times. Utility lighters of the type described herein generally contain a handle and an elongated lighting rod. The shape and operation of utility lighters allow for several advantages over normal means of producing a flame. Most significantly, due to the elongated nature of the lighting rod, utility lighters enable the operator to stand a safe distance away from the object to be ignited before actuating the lighter, thus avoiding a large number of potential accidents. In addition, utility lighters allow a flame to be produced in hard-to-reach or narrow places, where the human hand holding a match would not normally fit. Still, in the hands of children, or others who do not know how to safely and properly operate the lighter, such

lighters are as dangerous as any other spark and/or flame-producing device. Therefore, a need has been realized to equip utility lighters with safety features that minimize accidental or improper use by inexperienced persons, especially young children.

5 Many inventions have been created to address this safety-related concern. Generally, these inventions have sought to introduce safety mechanisms that disable automatic operation of either the spark-generation and/or the fuel-release function of the lighter. For example, some utility lighters provide for a
10 blocking mechanism, where the actuating trigger is blocked from moving the required distance for a spark to be generated. In these lighters, the locking mechanism is normally de-activated by sliding an "on/off" switch to the "on" position, or by other means, so as to remove the impediment from the actuating trigger's
15 operating path.

Although utility lighters of the type described above provide some level of safety, there is much room for improvement. Specifically, in these lighters, once the locking means (e.g., the on/off switch) is disabled, the lighter remains in the unlocked
20 state until the locking mechanism is activated again. Therefore, if the operator disables the locking mechanism in order to use the lighter, and then forgets to re-lock the lighter, the safety feature of the lighter is rendered useless, until the locking mechanism is again activated.

25 Other inventions have attempted to address the safety-related issues by impeding not the operation of the trigger, but that of the fuel-release mechanism. Of course, a utility lighter

containing such a mechanism would inhibit flame generation in the locked position as no fuel would be released until the locking mechanism has been deactivated. However, in these types of lighters, nothing prevents a spark from being generated. As such, the safety goals are only partially met in these types of lighters since young children handling the lighter could still create fires by operating the lighter in close proximity to a source of fuel or near carpets, paper, or other flammable material.

In order to address the above problems, some inventions have introduced locking mechanisms that are activated automatically after each use of the lighter. As such, in these lighters, two states of operation exist: the locked state and the operable state. In the locked state, neither a spark nor a flame can be generated. In contrast, in the operable state, the lighter is no longer locked, so that a flame can be generated. Although, in general, this improvement has alleviated some of the concerns mentioned above, there is still room for further improvement. Specifically, in most dual-state, automatic-locking lighters, once the lighter is unlocked and the trigger activated, the flame that is generated will subsist for as long as the trigger is held in the depressed position. In other words, once the locking mechanism is disabled, flame generation is a simple task involving depression of the trigger. This is of some concern since even young children might be able to achieve this task.

Therefore, there is a need for a device that not only achieves the stated safety goals in generating a flame, but also makes it difficult for inexperienced users and/or young children

to sustain the flame. The invention described herein offers such a combination. The invention requires that a safety button, protruding generally from the top portion of the lighter housing shell, be depressed simultaneously with a trigger before a flame
5 can be produced. In addition, the invention requires that the safety button, and not necessarily the trigger, be held in its activated state in order for the flame to be sustained; releasing the safety button after simultaneous activation of both the safety button and the trigger will cause the flame to be extinguished.

10 The unique structure of the safety button and the cam mechanism contained in the present invention provides for an optimum amount of safety as it makes it very difficult, if not impossible, for young children to operate the device. Young children are capable of carrying out only simple mental concepts.
15 As such, a young child wishing to operate the present invention would attempt to do so in the usual way, i.e., by pressing the trigger. However, due to the automatic locking mechanism of the device, the trigger will not move. This alone will act as a deterrent as most young children will simply abandon the device
20 after several unsuccessful attempts. This is true because a child operator must first recognize that both the trigger and the safety button must be operated simultaneously before a flame can be generated. Also, if the child does recognize that the slide-safety button plays a role in activating the lighter, then the
25 child operator must also recognize that the safety button must be operated prior to the trigger to generate a flame. These concepts

are generally too convoluted a concept for young children to grasp or appreciate.

Nevertheless, even if a young child were to be able to learn the proper operation of the device, he or she would probably still
5 be unable to actually operate the device. Given the relative location of the trigger and the safety button, operation of the present invention requires that the user be able to grasp the handle of the lighter in his or her hand, operate the trigger with the index finger, and simultaneously operate the safety button
10 with the thumb. Also, this invention also requires the user be able to operate the slide-safety button with the thumb, and operate the trigger with the index finger. This, in turn, requires not only a significant amount of manual dexterity, but also hands that are sufficiently large, namely, adult hands.
15 Moreover, successful operation of the device requires an amount of strength and pulp that are rarely found in the fingers of young children.

In addition, even if a child were to possess the mental capacity for understanding and learning the required process of
20 operation, a large enough hand, and the required amount of manual dexterity, strength, and pulp, so that he or she could somehow generate a flame, he or she would have to recognize a second concept: that the flame will not be sustained unless the safety button is held in its activated state. Again, this is a difficult
25 mental concept for a child to recognize and learn. Moreover, even if learned, the concept would be difficult for a child to operationalize given the above discussion regarding the mental and

physical limitations of young children. On the other hand, an adult user would have no difficulty operating the invention as the device requires no more than the simultaneous operation of two strategically positioned buttons.

5 In addition to all of the safety advantages described above, the invention described herein offers a significant reduction in cost, and a significant increase in ease, of manufacturing. The cam mechanism is an integrated, one-piece member that can perform the functions of two (2) or three (3) separate members in most
10 other utility lighters currently available on the market.

Moreover, the entire safety feature, as well as full operation of the device is generally enabled by the manufacture and use in the lighter of two (2) basic elements: the cam mechanism and the safety button. In addition, it is contemplated that these two
15 elements may even be combined, so that only one integrated structural member need be produced. This, of course, would lead to even more significant savings and simplicity in the manufacturing process.

20 3. SUMMARY OF THE INVENTION:

The primary object of this invention is to provide a safety mechanism for utility lighters so that children or inexperienced users will be less likely to inadvertently activate the lighter. Such a safety feature is especially important because young
25 children often play with lighters as toys and because lighters have mechanically moveable parts that make them attractive to children as toys.

Another object of the present invention is to prevent the generation of not only a flame, but even a spark. As noted previously, in a lighter where only the fuel-release mechanism is inhibited in the locked state, young children playing with the lighter can still use the lighter to create sparks. Depending on the child's surroundings, this can lead to the start of accidental fires if the child is operating the lighter near paper products or any other source of flammable material.

A further object of the invention described herein is to provide an improved device for maximizing safety in utility lighters without compromising ease of use. To this end, the addition of a safety button creates a simple additional step which, for the intended user, leaves the operation of the utility lighter as simple as it has always been to operate a regular utility lighter with no safety feature, yet, creates an additional mental step which acts as a deterrent for non-intended users.

Another object of this invention is to reduce the risk of unintended fires, especially by young children, by making it impossible for the flame to continue to burn unless two (2) separate functions are performed simultaneously and operation of a safety button is continued without interruption.

A final object of the present invention is to meet all of its safety goals while, at the same time, it maximizes ease of manufacturing and minimizes costs associated with manufacturing of parts.

The invention meets its objectives by providing a cam mechanism that integrates several structural elements. In a first

preferred embodiment, the cam mechanism consists of a cam lever, a fuel-release lever, and a return spring. Most significantly from a safety standpoint, the cam mechanism contains a cam lever that acts to lock the trigger in the inoperative position.

5 In a second preferred embodiment, the safety mechanism consists of a cam mechanism and a lever spring. The cam mechanism consists of a fuel-release lever and a safety button. The lever spring locks the trigger in the inoperative position.

Typically, a young child will attempt to activate the lighter
10 by depressing the trigger only. However, when this is done, the trigger will not move at all or significantly, so that neither a spark nor a flame will be generated. Since the trigger is locked in this position, repeated operation of the trigger by a child will yield the same unsuccessful results.

15 The only way to activate the lighter is to depress the safety button. In the first preferred embodiment, depressing the safety button moves the cam lever out of the path of the trigger, so that the trigger can now be depressed. In the second preferred embodiment, depressing the safety button moves the lever spring
20 out of the path of the trigger, so that the trigger can now be depressed.

Depression of the safety button also causes the fuel-release lever to move, so that, depending on the extent of pressure placed on the safety button, the fuel-release valve may be opened and
25 fuel released. As such, a second significant safety-related feature of the present invention is that a small amount of pressure on the safety button will release the trigger lock.

However, such pressure will not release sufficient fuel for a flame to be produced. That is, the most that can happen when the user presses the safety button slightly, and then depresses the trigger, is that a spark would be generated. To ignite the spark, the user would have to continue pressing the safety button further than is required to release the lock, so that sufficient fuel is released before the trigger is activated and a spark and flame are generated.

The above procedure ensures that even if a child were to be able to momentarily press the safety button to release the lock, he or she would still have trouble creating a flame, as doing so would require further pressure on the safety button. This is a simple, yet effective concept. Nevertheless, it is a concept that a young child operating the lighter must recognize and grasp before he or she can successfully operate the lighter. In most cases, the child either will not recognize the usefulness of the safety button or, if he/she does, he/she will not be able to simultaneously press the safety button far enough to create a flame. As such, the child will most likely abandon the lighter after several unsuccessful attempts.

Once the intended operator has pressed the safety button far enough to both unlock the trigger and provide adequate fuel release, the operator then presses the trigger in order to generate a flame. However, to sustain the flame, the operator must continue to hold the safety button in its activated position. This is a significant departure from lighters that are currently in the market. In most lighters currently in use, once a flame is

generated by depressing a trigger, the flame will subsist for as long as the operator continues to hold the trigger in its activated position. In contrast, in the present invention, the cam mechanism allows separation of fuel-release on the one hand, and spark generation on the other, so that spark generation will not necessarily lead to the production of a sustained flame.

It follows that, to successfully operate the present invention, the user must recognize that, once a flame has been generated, it is the safety button, and not the ignition trigger, that must be held in the activated position. This is another procedural step which creates a mental concept that is simple for the adult user to grasp and practice, but difficult for young children to either grasp or practice.

In the first preferred embodiment, once the user no longer needs the flame and the safety button is released, the return spring in the cam mechanism ensures that the cam lever, the fuel-release lever, and the safety button return to their original stationary positions, thus also automatically re-locking the trigger in the inoperable state. In the second preferred embodiment, the lever spring ensures that the fuel-release lever and the safety button all return to their original stationary positions when the safety button is released, thus also automatically re-locking the trigger in the inoperable state.

As can be understood from the above description, the invention disclosed herein achieves its safety objectives without making operation of the lighter any more cumbersome than a regular utility lighter. Specifically, the safety button is positioned in

such a way that operation of the lighter is very simple in experienced hands. An adult user familiar with the operation of utility lighters still needs to use only one finger to sustain the flame. This allows the user to operate the lighter in a safe, yet non-complicated manner.

This and other advantages of the present invention will become more apparent through the following description of the drawings and detailed description of the preferred embodiment.

4. BRIEF DESCRIPTION OF THE DRAWINGS:

Fig. 1 is a sectional view showing an embodiment of a child-resistant utility lighter according to the first preferred embodiment; and

Fig. 2 is a sectional view showing an embodiment of a child-resistant utility lighter according to the second preferred embodiment.

Fig. 3 is a perspective view of the child-resistant utility lighter;

Fig. 4 is an environmental view of the child-resistant utility lighter in use;

Fig. 5 is a sectional view of the third embodiment of the lighter without the trigger, the safety button, the locking spring, or the stopper tab;

Fig. 6 is a sectional view of the third embodiment of the lighter;

Fig. 7 is a sectional view of the third embodiment with the trigger being depressed in the direction of the arrow while the trigger is in the locked position;

Fig. 8 is a sectional view of the third embodiment with the safety button being translated in the direction of the arrow and the trigger being depressed in the direction of the arrow;

Fig. 9 is a like view with the trigger fully depressed;

Fig. 10 is a perspective view of the right side of the safety button;

Fig. 11 is a perspective view of the left side of the safety button;

Fig. 12 is a perspective view of the trigger of the third embodiment;

Fig. 13 is a sectional view of the fourth embodiment;

Fig. 14 is a sectional view of the fifth embodiment of the lighter without the trigger, the safety button, the leaf spring, or the stopper tab;

Fig. 15 is a sectional view of the fifth embodiment of the lighter;

Fig. 16 is a sectional view of the fifth embodiment with the trigger being depressed in the direction of the arrow while the trigger is in the locked position;

Fig. 17 is a sectional view of the fifth embodiment with the safety button being translated in the direction of the arrow and the trigger being depressed in the direction of the arrow; and

Fig. 18 is a perspective view of the trigger and the locking lever of the fifth embodiment.

5. DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS:

5 A general description of the piezoelectric utility lighter (1) will be provided before presenting a detailed description of the improvement in the safety feature that constitutes the invention.

10 Generally, the elements of the utility lighter (1) include a lighter housing (10), a lighting rod attached to the forward end of the lighter housing via engagement means such as a support ring which slides over the overlapping portions of the lighter housing and lighting rod, a fuel tank (30) (Fig. 5), a piezoelectric unit (40), and a trigger (100).

15 The lighter housing (10) is comprised of two shells, cut along the longitudinal axis of the lighter (1). Figs. 1, 2, and 5 show one of these shells. The lighter housing (10) has a back end (10a) and a forward end (10b) (Fig. 5), where the forward end is equipped with engagement means such as a support ring (Fig. 5) to
20 engage the lighting rod. The lighting rod, which typically has a cylindrical cross section, has a free end which constitutes the tip of the lighter (1) and an engagement end which connects to the forward end of the lighter housing. Where the forward end of the lighter housing and the engagement end of the lighting rod
25 overlap, there is provided a support ring (Figs. 4, 5) which slides over and maintains the lighter housing-lighting rod combination.

The lighter (1) is equipped with a fuel tank (30) near the back end (10a) of the lighter housing (10). The fuel tank (30) has a bottom portion (30a) facing the back end (10a) of the lighter housing, and a top portion (30b) pointing towards the forward end of the lighter housing. A fuel-release valve (31) is attached to the top portion (30b) of the fuel tank. This valve is spring loaded so that it is normally urged to the closed position. The valve is also provided with a gas tube (32) which extends through the lighting rod and to a discharge nozzle at the free end of the lighting rod. The valve is opened via the operation of a fuel-release lever (70) from the translation of the safety button or release lever. Finally, a flame-adjusting knob (33) is provided on the valve (31) which can be turned to adjust the amount of fuel released and, thus, the height of the resultant flame.

The next element of the lighter (1) is a piezoelectric or fuel ignition unit (40). This unit is fitted within the top portion (30b) of the fuel tank and protrudes from said top portion. The upper section of the piezoelectric unit (40) constitutes the sliding section (41). The sliding section (41) has a contact surface (42) that is in contact with an undersurface (102) of trigger (100). Operation of the piezoelectric unit (40) creates an electric discharge that is carried to the free end of the lighting rod via a wire.

One of the primary elements of the first preferred embodiment (Fig. 1) is a cam mechanism (60). The cam mechanism has a hub (61), as well as three projections that extend in generally

different directions. These projections are: a fuel release lever (70), a cam lever or latch (80), and a return spring (90).

The hub (61) is held in place by a cam-support pin (50). The cam-support pin is a projection that extends from the inner
5 surface of one of the lighter housing shells (10) in a direction that is perpendicular to the longitudinal axis of the lighter (1). The hub fits onto and is supported by the cam-support pin.

The fuel-release lever (70) has one end (71) that is located between the valve (31) and the flame-adjusting knob (33), and an
10 opposing end that is integral with the hub (61) of the cam mechanism (60).

The cam lever or latch (80) has one end that is integral with the hub (61) of the cam mechanism (60) and an opposing free end that constitutes the cam-lever edge (81). The cam lever also has
15 an upper surface (82), a lower surface (83), and a cavity (84). The cavity (84) houses a safety-button pin (123) of a safety button (120).

The return spring (90) also has one end that is integral with the hub (61) of the cam mechanism (60) and an opposing free end
20 (91). The return spring further consists of an upper surface (92) and a lower surface (93), where the lower surface rests on a projection (15) that is fixedly attached to the inner surface of one of the lighter housing shells (10).

The next primary element of the first preferred embodiment is
25 the trigger (100). The trigger is slidably mounted between the two shells of the lighter housing (10). As in conventional utility lighters, the trigger is allowed to slide back and forth

along the longitudinal axis of the lighter (1). The trigger has an operation section (101) that protrudes from the lighter housing (10) so as to be operated by a finger of the user. Generally, the operation section (101) has a surface that is slightly curved so as to appear concave. However, the invention described herein is amenable to different degrees of curvature for the operation section (101) of the trigger.

The trigger (100) also has an undersurface (102) that makes contact with the contact surface (42) of the sliding section (41) of the piezoelectric unit (40). In addition, the trigger (100) is integral with a trigger tab (103) and a stopper tab (110). The trigger tab (103) is a projection that makes contact with the upper surface (82) of the cam lever (80). The stopper tab (110) is typically placed underneath the trigger tab (103) and has a contact edge (111) that engages the cam lever edge (81).

The next primary element of the first preferred embodiment is a safety button or release lever (120). The safety button (120) is slidably fitted within the top surface of the lighter housing shell and has an operation section or external end (121) that protrudes from this top surface of the lighter housing. The safety button has a lower surface (122) that is integral with a safety-button pin (123), which pin (123) is in contact with the cam lever (80) via the cavity (84) in said cam lever. The safety button (120) is also integral with a set of flanges (124) that can make contact with the inner portion of the top surface of the lighter housing shell, thus limiting the range of motion of the safety button (120).

In the first preferred embodiment (Fig. 1), the primary elements of the safety-related invention described herein, as well as the interaction between these and the other, more conventional, elements of the utility lighter can be further defined as follows.

5 In the first preferred embodiment, the hub (61) of the cam mechanism (60) is fitted onto and supported by the cam-support pin (50), so that the hub (61) is capable of rotating around the cam-support pin (50). In order to operate the lighter (1), the user must press the trigger (100) to create a spark, and release fuel
10 so that a flame can be generated. However, when the user attempts to press the trigger (100), the trigger will not move significantly or at all.

In the inoperable state (non-operational lighting position), the trigger tab (103) is in contact with the upper surface (82) of the cam lever (80). The trigger (100) is integral with a stopper
15 tab (110) whose contact edge (111) engages the cam-lever edge (81) of the cam lever (80). This acts as a locking mechanism which must be released before the trigger can be moved. To release the lock, the user must press the safety button (120) by pushing on or
20 manipulating the safety button operation section (121). When the safety button (120) is depressed, the motion of the safety button (120) is translated to the cam lever (80) via the safety-button pin (83) as resistance is provided by the return spring (90) pressing against the projection (15).

25 Initially, the cam lever or latch (80) moves, so that its cam-lever edge (81) is disengaged from the contact edge (111) of the stopper tab (110) (operational position). In addition, the

initial pressing of the safety button (120) will cause the fuel-release lever (70) to also move slightly. However, this movement will be insufficient to release an amount of fuel that is adequate for flame production.

5 With the locking mechanism disengaged, the user can now press the trigger (100) in order to create a spark. As the operation section (101) of the trigger (100) is pushed, the undersurface (102) of the trigger (100) contacts the contact surface (42) of the sliding section (41) of the piezoelectric unit (40). In this way, as the trigger (100) is activated, so is the piezoelectric unit (40), so that a spark is generated when the sliding section (41) has moved back far enough.

10 Without more, the operational procedure described above will only produce a spark. In order to produce a flame, the operator must continue to push the safety button or release lever (120), thereby further moving the cam lever (80). This, in turn, causes further rotation of the hub (61), which causes the fuel-release lever (70) to open the fuel-release valve (31) and release fuel. Now, with the safety button (120) held in this position, 15 depression of the trigger (100) will allow a flame to be generated.

20 Once a flame has been generated, it can be sustained only if fuel continues to be supplied. As explained above, this will only occur if the safety button (120) is held in position and not released after a flame has been generated. Simply holding the 25 trigger (100) in the activated state will not sustain the flame. That is, even though, after the lighter has been unlocked,

depression of the trigger (100) might cause the upper surface (82) of the cam lever (80) to be held underneath the bottom surface of the stopper tab (110), the hub (61) of the cam mechanism (60) has not rotated enough at this point for the fuel-release lever (70) to be able to move and sufficiently open the fuel-release valve (31).

Once the flame is no longer needed, the safety button (120) is released. This allows both the cam lever (80) and the fuel-release lever (70) to return to their stationary positions under the urging influence of return spring (90). Once in this position, the cam-lever edge (81) again engages the contact edge (111) of the stopper tab (110), thereby automatically re-locking the lighter. Finally, as the safety button (120) moves to its stationary position, it is stopped in that position when flanges (124) reach the inner portion of the top surface of the lighter housing shell.

In the second preferred embodiment (Fig. 2), one of the primary elements of the lighter is the cam mechanism (60). The cam mechanism (60) has a hub (61) and two projections: a fuel-release lever (70) and a safety button (120).

The cam mechanism (60) is held in place by a cam-support pin (50). The cam-support pin is a projection that extends from the inner surface of one of the lighter housing shells (10) in a direction that is perpendicular to the longitudinal axis of the lighter (1). The hub (61) of the cam mechanism (60) fits onto and is supported by the cam-support pin.

The fuel-release lever (70) has one end (71) that is located between the valve (31) and the flame-adjusting knob (33), and an opposing end that is integral with the hub (61) of the cam mechanism (60).

5 The safety button (120) is slidably fitted within the top surface of the lighter housing shell (10) and has an operation section (121) that protrudes from this top surface. The safety button has a safety button projection (151) that contacts the lever spring (150). The safety button has a lower portion (122)
10 that is integral with the hub (61). A safety button stop (152) limits the downward range of motion of the safety button. The safety button stop is a projection that extends from the inner surface of one of the shells in a direction that is perpendicular to the longitudinal axis of the lighter (1).

15 The next primary element of the second preferred embodiment is the lever spring (150). The lever spring has one end that constitutes a lever spring edge (112) and an opposing end that is fixed to a spring projection (15) that is fixedly attached to the inner surface of one of the lighter housing shells.

20 The next primary element of the second preferred embodiment is the trigger (100). The trigger is slidably mounted between the two shells of the lighter housing (10). As in conventional utility lighters, the trigger is allowed to slide back and forth along the longitudinal axis of the lighter (1). The trigger has
25 an operation section (101) that protrudes from the lighter housing so as to be operated by a finger of the user. Generally, the operation section has a surface that is slightly curved so as to

appear concave. However, the invention described herein is amenable to different degrees of curvature for the operation section of the trigger.

The trigger (100) also has an undersurface (102) that makes contact with the contact surface (42) of the sliding section (41) of the piezoelectric unit (40). In addition, the trigger is integral with a trigger tab (103) and a stopper tab (110). The trigger tab is a projection that makes contact with the upper surface of the lever spring (150). The stopper tab is typically placed underneath the trigger tab and has a contact edge (111) that engages a lever spring edge (112).

In the second preferred embodiment (Fig. 2), the primary elements of the safety-related invention described herein, as well as the interaction between these and the other, more conventional, elements of the lighter can be further defined as follows:

In the second preferred embodiment, the hub (61) of the cam mechanism (60) is fitted onto and supported by the cam-support pin (50), so that the hub is capable of rotating around the cam-support pin (50). In order to operate the lighter (1), the user must press the trigger (100) to create a spark, and release fuel so that a flame can be generated. However, when the user attempts to press the trigger, the trigger will not move significantly or at all.

When the lighter is in the locked position, the trigger tab (103) is in contact with the upper surface of the lever spring (150), and the contact edge (111) of the stopper tab (110) engages the lever spring edge (112). Engagement of these edges acts as a

locking mechanism which must be released before the trigger can be moved. To release the lock, the user must depress the safety button or release lever (120) by depressing the safety button operation section or external end (121) of the safety button.

5 When the safety button is depressed, the motion of the safety button is translated to the lever spring via the safety-button projection (152) as resistance is simultaneously provided by the flexing of the lever spring (150).

10 Initially, the lever spring (150) moves, so that its lever spring edge (112) is disengaged from the contact edge (111) of the stopper tab (110). In addition, the initial depression of the safety button (120) will cause the fuel-release lever (70) to also move slightly. However, this movement will be insufficient to release an amount of fuel that is adequate for flame production.

15 With the locking mechanism disengaged, the user can now press the trigger (100) in order to create a spark. As the operation section (101) of the trigger is pushed, the undersurface (102) contacts the contact surface (42) of the piezoelectric unit (40). In this way, as the trigger is activated, so is the piezoelectric unit, so that a spark is generated when the sliding section (41) has moved back far enough.

20 Without more, the operational procedure described above will only produce a spark. In order to produce a flame, the operator must continue to push the safety button (120), thereby causing further rotation of the hub (61), which causes the fuel-release lever (70) to open the fuel-release valve (31) and release fuel. The safety button stop (152) limits the distance the safety button

can be depressed. Now, with the safety button (120) held in this position, depression of the trigger (100) will allow a flame to be generated.

Once a flame has been generated, it can be sustained only if fuel continues to be supplied. As explained above, this will only occur if the safety button (120) is held in the depressed position and not released after a flame has been generated. Holding the trigger (100) in the activated state alone will not sustain the flame.

Once the flame is no longer needed, the safety button (120) is released. This allows the fuel-release lever (70) to return to its stationary position under the urging influence of the lever spring (150). Once in this position, the lever spring edge (112) again engages the contact edge (111) of the stopper tab (110), thereby automatically re-locking the lighter.

In the third embodiment of the invention, the next element of the lighter (1) is a piezoelectric unit (40) (Fig. 6). This unit is fitted within the top portion (30b) of the fuel tank and protrudes from said top portion. The upper section of the piezoelectric unit (40) constitutes the sliding section (41). The sliding section (41) contacts the trigger (100). Actuation of the piezoelectric unit or fuel ignition unit (40) creates an electric discharge that is carried to the free end of the lighting rod via a wire (242).

The present invention includes a trigger (100), a locking mechanism, and a safety button (270).

The trigger (100) is slidably mounted between the two shells of the lighter housing (10). As in conventional utility lighters, the trigger (100) is allowed to slide back and forth along the longitudinal axis of the lighter (1). The trigger (100) has an operation section (101) that protrudes from the lighter housing (10) so as to be operated by a finger of the user.

Generally, the operation section (101) has a surface that is slightly curved so as to appear concave. However, the invention described herein is amenable to different degrees of curvature for the operation section (101) of the trigger (100). The trigger (100) contacts the sliding section (41) of the piezoelectric unit (40). Full depression of the trigger results in actuation of the piezoelectric unit.

The locking mechanism prevents the trigger from being depressed until the safety button or release lever (270) has been translated into the active position. The safety button, when in the active position, opens the valve (31) to release fuel.

The safety button (270) is slidably mounted in the lighter housing (10). The safety button includes a contact surface (274) (Figs. 10 and 11), a return spring (275), a fuel-releasing segment (276), and a unlocking segment (277). The contact surface protrudes beyond the lighter housing for receiving the user's finger. The safety button is translated from its initial position to its active position when the user pushes the safety button forward in the direction of the arrow A (Figs. 8 and 9). The return spring constantly urges the safety button into its initial position.

The fuel-releasing segment (276) of the safety button (270) is located between the valve (31) and the flame-adjusting knob (33). The unlocking segment (277) of the safety button is located above the trigger (100). When the safety button is translated by being pushed forward, the fuel-releasing segment opens the valve, and fuel is released.

The third preferred embodiment of the invention includes a trigger (100) (Fig. 6), a stopper tab (273), a safety button (270), and a locking spring (272). The trigger (Fig. 12) includes an operation section (101), a locking lever (271), a projection (278), and a locking spring (272). The stopper tab is formed in the top portion of the fuel tank (30). The locking spring is mounted to the lighter housing (10) and is constantly urging the trigger into the locked position.

Depression of the trigger (100) alone (Fig. 7) without also activating the safety button (270), results in the locking lever (271) engaging the stopper tab (273). Thus preventing actuation of the piezoelectric unit (40).

Activation of the safety button (270) causes the unlocking segment (277) (Fig. 8) to interact with the projection (278). This interaction between the unlocking segment and the projection forces the locking lever (271) downward thus disengaging it from the stopper tab (273). The projection must be sufficiently large to move the locking lever a sufficient distance such that it cannot engage the stopper tab. As a result, the trigger (100) can be fully depressed thus actuating the piezoelectric unit (40).

Once a flame has been generated, it can be sustained only if fuel continues to be supplied. Simply holding the trigger (100) in the depressed state will not sustain the flame. Fuel continues to be supplied only as long as the safety button (270) is held in the active position.

When the safety button or release lever (270) is released the return spring (275) urges the safety button into its initial position. As a result, the locking lever (271) returns to the locked position and the valve (31) returns to the closed position. Once in the locked position, the locking lever (271) re-engages the stopper tab (273). Therefore, the lighter (1) is thereby automatically re-locked.

The fourth preferred embodiment of the invention includes a trigger (100) (Fig. 13), a safety button (270), a locking lever (271), and a locking spring (272).

The locking lever (271) has a first end (281) and a second end (291). The second end of the locking lever is pivotally mounted to the lighter housing (10). The trigger (100) includes a stopper tab (273). The stopper tab (273) engages the first end of the locking lever (271). The stopper tab blocks the first end of the locking lever, and as a result, the trigger cannot be squeezed to actuate the lighter. The locking spring (272) urges the locking lever into the locked position.

The unlocking segment (277) of the safety button (270) includes a ramped portion (283). When the safety button is activated, the ramped portion contacts the locking lever (271) and depresses the locking lever. When the locking lever is depressed,

the locking lever is disengaged from the stopper tab (273). Thus activating the safety button unlocks the trigger (100), and the trigger can then be depressed and the piezoelectric unit (40) actuated.

5 Once a flame has been generated, it can be sustained only if fuel continues to be supplied. Simply holding the trigger (100) in the depressed state will not sustain the flame. Fuel continues to be supplied only as long as the safety button (270) is held in the active position.

10 When the safety button (270) is released, the return spring (275) urges the safety button into the initial position. Once the safety button is in its initial position, the locking lever (271) returns to the locked position under the force of the locking spring (272) and the valve (31) returns to the closed position.
15 When the locking lever returns to the locked position, the locking lever (271) again engages the stopper tab (273). The lighter (1) is thereby automatically re-locked.

20 The fifth embodiment of the invention (Figs. 14-18) includes a trigger (100), a stopper tab (273), a safety button (270), a locking lever (271), and an arm locking spring or arm spring (284).

25 The locking lever (271) has a first end (340), a second end (341), and a projection (278). The second end of the locking lever is pivotally mounted to a pivot point projection (342) extending from the lighter housing (10). The trigger (100) includes the stopper tab (273). The stopper tab engages the first end of the locking lever. The stopper tab blocks the first end of

the locking lever, and as a result, the trigger cannot be squeezed to activate the lighter (1).

The arm spring (284) has an arm (285) and a coiled end (286). The coiled end of the arm spring is coiled and sized to be
5 securely mounted to the pivot point projection (342). The arm extends radially outward from the coiled end of the arm spring and is biased against the bottom surface of the locking lever (271). The arm spring urges the locking lever into the locked position.

The unlocking segment (277) of the safety button (270)
10 includes a ramped portion (283). When the safety button is activated, the ramped portion contacts the projection (278) of the locking lever (271) and depresses the locking lever. The projection must be sufficiently large to move the locking lever a sufficient distance such that it cannot engage the stopper tab
15 (273). When the locking lever is depressed, the locking lever is disengaged from the stopper tab (273). Thus, activating the safety button unlocks the trigger (100), and the trigger can then be depressed and the piezoelectric unit (40) actuated.

Once a flame has been generated, it can be sustained only if
20 fuel continues to be supplied. Simply holding the trigger (100) in the depressed state will not sustain the flame. Fuel continues to be supplied only as long as the safety button or release lever (270) is held in the active position.

When the safety button (270) is released, the return spring
25 (275) urges the safety button into the initial position. Once the safety button is in its initial position, the locking lever (271) returns to the locked position under the force of the arm spring

(284), and the valve (31) returns to the closed position. When the locking lever returns to the locked position, the locking lever again engages the stopper tab (273). The lighter (1) is thereby automatically re-locked.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2